

LEDX.NO

LED expert AS
Torpumveien 543
1788 Halden

E-post: post@ledx.no
Tlf: 909 54 606



LED POST TOP LIGHT



RoHS



Ideal for parking lot, playground, square, park, highway, greenbelt
golf course, and etc.

Parameters

LEDX.NO

| | |
|-----------------|---------------------------|
| WATTAGE | 50/80/100/150/200/240W |
| DRIVER | MEANWELL |
| LAMP EFFICIENCY | 160LM/W \pm 5% |
| LIGHT SOURCE | LUMIEDS |
| CRI | Ra>70/80 |
| CCT | 2700-6500K |
| RATED VOLTAGE | AC 100-240V 277V~,50/60Hz |
| POWER FACTOR | >0.95 |
| BEAM ANGLE | 60°/90°/120° |
| IP GRADE | IP66 |
| OPERATING TEMP | -40°C~60°C |
| POLE SIZE | 60/80mm |



50W

8,000LM \pm 5%
3.6kg \pm 5%
 ϕ 380*162mm

80W

12,800LM \pm 5%
4.0kg \pm 5%
 ϕ 380*162mm

100W

16,000LM \pm 5%
4.1kg \pm 5%
 ϕ 380*162mm

150W

24,000LM \pm 5%
4.2kg \pm 5%
 ϕ 380*162mm

200W

32,000LM \pm 5%
6.0kg \pm 5%
 ϕ 500*168mm

240W

38,400LM \pm 5%
6.0kg \pm 5%
 ϕ 500*168mm

▶ Highly Efficient System

160Lm/w lighting output

▶ IP66

Integrated design protect the light from water & dirt

▶ High robustness

Provide long-term lighting

▶ Unique Design

Decorate your public space

▶ Hydrophobic surface

Too smooth to gather any dirt

▶ Rust resistant

All aluminium body

Light Distribution

60° /90° /120° available



60°



90°



120°

