

TECHNICAL FEATURES / CARATTERISTICHE TECNICHE



ITEM	FIXTURE	[KEY features]
LEDs	RGBW	14 (5050-20W) RGB-NW (white 4000K)
Total light power		110W
Lumen		R1700, G3400, B650, W3500
Optics		15° (38mm lenses) PMMA 8N and ultra clear white tempered glass on request: 8°, 25, 40°, 60°, 10°x30°
Power consumption		115W - 0.50A@230V
Voltage range		180/240VAC, 47-63Hz, Active PFC: >0.95@230V
Control - Setup		Standard interface: RS-485-Protocol USITT DMX512, optocoupled input RDM DMX-RDM/DRS
Connections		IN-OUT DMX 4pins IP67 connectors - 1,5mt 3x1 cable
Physical		247x190x300 mm
Weight		4,6 Kg
Operating temperature range		Ta 40°C
Control		Standard interface: RS-485; opto-couplet bi-directional Protocol: USITT DMX 512, RDM Protocol > Integral Wireless DMX control (receiver) is available as an option (art. WI PCB-REC).
Connections		Signal: 4pin IP 67 connector (male-female) possibility to link up to 32 devices in chain
Setup		RDM Control/configuration or individually by DRS (remote control device) Dedicated DMX channel for white balance DMX or Auto mode with Master-Slave function Halogen simulation CYM simulation Flicker-free function Smooth dimming function
DMX channels		9CH mode, 6CH mode, 5CH mode, 4CH mode



OPTIONAL ACCESSORIES / ACCESSORI OPZIONALI

- Barn-door
- Wireless DMX receiver