

LEDX.NO

LED expert AS
Torpumveien 543
1788 HaldenE-post: post@ledx.no
Tlf: 909 54 606

ITEM	FIXTURE	100cm [KEY features]	50cm [KEY features]
LEDs	RGBW	28 RGB-NW (white 4000K)	14 RGB-NW (white 4000K)
Lumen		Red 800, Green 1200, Blue 400, White 1250	Red 400, Green 600, Blue 200, White 625
Optics		24° (23mm lenses) PMMA 8N and ultra white tempered glass On request: 12°, 36°, 10°x30°, 15°x55°, holographic filter 10°x60° to match with narrow beam	
Power consumption		60W - 0,28A@230V	32W - 0,15A@230V
Power supply		230/240VAC; 47-63Hz; Active PFC: >0,95@230V	230/240VAC; 47-63Hz; Active PFC: >0,90@230V
Physical		1005x40x60 mm (profile dim.)	525x40x60 mm (profile dim.)
Weight		2 Kg	1 Kg
Control		Standard interface: RS-485, optocoupled input - Protocol USITT DMX512, RDM	
Connections		IN-OUT M25 fast-lock connector with POWER and SIGNAL in one	
Setup		DMX - RDM/DRS	
DMX Channels		CH4, CH5, CH6, CH9 mode	

Operating temperature range	Ta 40°C
Control	Standard interface: RS-485; opto-couplet bi-directional Protocol: USITT DMX 512, RDM Protocol
Connections	IN-OUT M25 fast-lock connector with POWER and SIGNAL in one.
Setup	RDM Control/configuration or individually by DRS (remote control device) Dedicated DMX channel for white balance DMX or Auto mode with Master-Slave function Halogen simulation CYM simulation Flicker-free function Smooth dimming function
DMX channels	9CH mode, 6CH mode, 5CH mode, 4CH mode

