



auch mit Durchgangsverdrahtung erhältlich
also available with through-wiring
aussi disponible câblage traversant
ook met doorgaande bedrading



Explosion-proof LED built-in and surface mounted lamp with high light output. Ideal for the integration in machines, vehicles and all kind of electric devices.

- Illuminant: 24 POWER LEDs / 6500 K
- Protection tube: polycarbonate, shock-resistant, 50 mm Ø
- End cap: aluminium, black anodized
- Fixation: incl. 2 fixing clamps made of plastic
- Protection category: IP68 -50 m / 5 h
- Protection class: II / III
- Cable: 10 m H07BQ-F 2 x 1,50 mm²
- Voltage: 230 V / 110 V / 24 V
- Special requests - as covered by our Ex-certification - can be fulfilled.

Number LED	Volt	Ampere	Lumen	Protection Class	Protective Tube	IP	Cable	Plug	EEC
24	230 V AC	0,075	1550 lm	II	Polycarbonat	IP68	10 m H07BQ-F	ohne w/o	A F
24	110 V AC/DC	0,135	1600 lm	II	Polycarbonat	IP68	10 m H07BQ-F	ohne w/o	A F
24	24 V AC/DC	0,550	1650 lm	III	Polycarbonat	IP68	10 m H07BQ-F	ohne w/o	A F

Dimensions



Dimensions in mm

a	b	c	d	e	f	g	h	i
35	25	500	165	45	25	53	50	770

Weight: ca. 2,2kg

ATEX Identification

ATEX-Nr.: TÜV 18 ATEX 8191 X

II 2 G Ex eb mb op is IIC T4 Gb

II 2 D Ex tb op is IIIC T105° Db IP68

Gerätegruppe / Device group:

II

Kategorie / Category:

2G / 2D

Gefahrenzone / Hazard zone:

1,2 / 21, 22

Temperaturklasse / Temperature class:

T4

T_{amb}:

-20°C - +40°C