



LED SPOTLIGHT

LEDX.NO

LED expert AS
Torpumveien 543
1788 Halden

E-post: post@ledx.no
Tlf: 909 54 606



LED

4100
Lumen

24V
-
48V

IP65



optional erhältlich / optionally available



Magnetbefestigung
magnetic fixing
fixation magnétique
magnetische bevestiging



Aufhängehaken
suspension hook
crochet
haken



Standfuß
stand
cadre auxilliare
sub frame



Robust ex-proof LED worklight with bright light. Dazzle-free light based on special prismatic-shaped cover.

- Robust LED spotlight, 81 POWER LEDs
- Voltage 24V - 48V AC/DC
- Plastic housing, antistatic
- Width, uniform illumination
- Positionable horizontally or vertically
- Protection category IP65
- Cable: 10 m H07RN-F (opt. 30m)
- optionally equipment available

Number LED	Volt	Watt	Lumen	Housing	IP	Cable	Plug	Weight
81	24V-48V AC/DC	35W	4100	Plastik / plastic	IP65	10m H07RN-F	ohne w/o	3,5 kg
81	24V-48V AC/DC	35W	4100	Plastik / plastic	IP65	30m H07RN-F	ohne w/o	3,5 kg

Dimensions



Dimensions in mm

a	b	c
388	147	319



ATEX Identification

II 2 G Ex ib mb IIC T4 Gb

II 2 D Ex ib mb IIIC T135° Db

Gerätegruppe / Device group:

II

Kategorie / Category:

2G / 2D

Gefahrenzone / Hazard zone:

1,2 / 21, 22

Temperaturklasse / Temperature class:

T4

T_{amb}:

-20°C - +50°C