

LEDX.NO

LED expert AS  
Torpumveien 543  
1788 Halden

E-post: [post@ledx.no](mailto:post@ledx.no)  
Tlf: 909 54 606

IP44/IP20



## Description

### THE LUMINAIRE IS IN PREPARATION.

Interior LED luminaire designed to illuminate office buildings, schools, commercial and public spaces. The low-profile body is made of painted aluminium profile in RAL 9003 shade, which ensures high durability and long service life. The luminaire is equipped with an optical microprismatic cover (MP) for uniform light distribution without glare, suitable for work and learning environments. The IP44 rating allows for use in areas with increased humidity or dust. Designed for energy efficient operation and long life, the luminaire is a reliable solution for quality interior lighting.

## Specifications

### **Operating voltage:**

220-240 V / 50/60 Hz AC

### **Source:**

LED, 4000K, CRI +80, MacAdam5

### **Housing:**

Painted aluminium profile RAL 9003

### **Cover:**

**MP** – optical microprismatic cover

### **Fastening:**

Installation in ceiling modules 600 with visible support rail systems, minimum height of free cavity in the ceiling 200 mm, suspension with cable hangers (66995), fixing in the plasterboard hole with brackets (66994).

### **Connection:**

Connection of the ballast to the luminaire using a cable with a connector.

### **Calculated lifetime – LED modules:**

L80B10 Ta 25 – 50 000 h

L70B10 Ta 25 – 54 000 h

---

## On order

**OND** – ON/OFF lamp (allows looping)

**OD2** – DALI2 luminaire

**LM3A** – ON/OFF luminaire + 3h emergency, AUTOTEST (allows looping)

**LA3D2** – DALI2 luminaire + emergency 3h, AUTOTEST (allows looping)

**LD3D2** – DALI2 luminaire + emergency 3h, DALI (allows looping)