



Parkmaster med universal fotplate

	Lyspunkt- høyde	Maks armaturflate Vref m/s				c/c bolter	Topp- diameter	Vekt
		24	27	29	31			
Varmforsinket								
	3,0 m	1,09	0,88	0,77	0,68	160/200	ø60	25
	3,5 m	0,86	0,69	0,60	0,53	160/200	ø60	28
	4,0 m	0,70	0,55	0,47	0,41	160/200	ø60	30
	5,0 m	0,63	0,48	0,40	0,34	160/200	ø60	37
	6,0 m	0,42	0,31	0,25	0,20	160/200	ø60	44
Pulverlakkert								
	3,0 m	1,09	0,88	0,77	0,68	160/200	ø60	25
	3,5 m	0,86	0,69	0,60	0,53	160/200	ø60	28
	4,0 m	0,70	0,55	0,47	0,41	160/200	ø60	30
	5,0 m	0,63	0,48	0,40	0,34	160/200	ø60	37
	6,0 m	0,42	0,31	0,25	0,20	160/200	ø60	44

Koniske parkmaster

	Lyspunkt- høyde	Maks armaturflate Vref m/s				c/c bolter	Topp- diameter	Vekt
		24	27	29	31			
Varmforsinket								
	3,5 m	0,93	0,75	0,65	0,58	160	ø76	32
	4,0 m	0,53	0,41	0,35	0,30	160	ø60	34
	4,0 m	0,92	0,74	0,64	0,56	160	ø76	37
	5,0 m	0,55	0,42	0,36	0,31	160	ø60	42
	5,0 m	0,60	0,46	0,39	0,34	160	ø76	47
Pulverlakkert								
	3,5 m	0,93	0,75	0,65	0,58	160	ø76	32
	4,0 m	0,53	0,41	0,35	0,30	160	ø60	34
	4,0 m	0,92	0,74	0,64	0,56	160	ø76	37
	5,0 m	0,55	0,42	0,36	0,31	160	ø60	42
	5,0 m	0,60	0,46	0,39	0,34	160	ø76	47

